

Theoretical working capacity: 6300 m / h



### PRODUCT SPECIFICATIONS



Ride-on machine with traction



Power supply 36 V / 320 Ah



Cleaning width 900 mm



Brushes pressure adjustable max. 140 kg



Battery autonomy 3,5 - 4,5 h



Solution tank / recovery tank 180 / 190 l



Disc brushes 2 x 460 mm



Brushes speed 162 rpm

- Squeegee width: 1175 mm
- Brushes motor: 2x700 W
- Motion system: automatic
- Maximum gradient: 10%
- Suction motor: 2x570 W
- Suction vacuum: 190 mbar
- Machine dimensions: L: 1962  
with rollbar H: 1865  
without rollbar H: 1613  
W: 985
- Machine weight w/o battery: 458
- Traction motor: 1200 W
- Movement speed: 7 km/h
- Battery compartment: L: 540  
H: 460  
W: 620
- Class: III
- Protection level: IP X3
- Loudness: <70 db (A)

**Power supply 36V**, allows the use of powerful motors and high efficiency.

- Motorcycle-wheel in AC, facilitates the maintenance and provides incomparable working comfort, especially in a high percentage ramp.
- Pressure of the important brushes on a working width of 900mm.
- 2 x 3-stages suction motors - silent mode available.
- Water capacity 180 / 190 Lts

**A lot of efforts has been done on ergonomics and comfort for the operator.**

3 levels of adjustment of the driving position:

- Seat
- Steering wheel
- Footrest

**Simplified maintenance**

Foldable arch for easy transport.

Large recovery tank inspection hatch.

Recovery tank drain hatch.

**Eco systems available as an option:**

- 3S = control of water consumption.
- 3SD = embedded chemistry.
- O3 = cleaning and disinfecting without chemistry.

