






# Onyx 43


 Machine walk behind traction by the brush

 Working autonomy 1H50


 Batteries 24V 34Ah

 Working width 430mm

 Tanks solution/recovery 23 / 23 l

 Brush - pad diameter 430mm/17"

 Brush pressure 35 kg

 Brush speed 150 rpm



Theoretical working capacity

## 1500 m<sup>2</sup>/h

The great tank capacity added to the reduced external dimensions permit to have a machine that has both a big working autonomy and the possibility to work also in very small environments.

The recovery tank can be emptied with a suitable exhaust hose. Distinctive element is the squeegee. In fact, its system permits to rotate completely, both to the right and to the left, enabling the drying even during reverse movements.

The handle bar is adjustable in height and it can be folded completely onto the tanks, this to simplify transfers. In this position, any intervention of maintenance on the brush or the squeegee results to be considerably easier.

Strong points :

- Handling and ergonomic
- Quality of suction = perfect dry floor
- Drying in reverse mode

Water consumption= 0,49l/min

Suction width	510mm
Traction	by the brush
Brush motor	450 Watt
Maxi. gradient	2%
Suction motor	300 Watt
Depression	82 mbar


Dimensions :

Length	793 mm
Height	600 mm
Width (without squeegee)	480 mm
Machine weight (with batteries)	86,5 kg

Battery compartment :

Length	346 mm
Width	207 mm
Height	210 mm

Class	III
Protection level	IP 23
Noise level	< 70 dB (A)



We reserve the right to make technical modifications.

